



## Features

- Eliminates laborious folding, stuffing and sealing tasks
- Attaches easily to your HP LaserJet 4014, 4015, and 4515
- Automatically prints, folds and seals pressure seal documents
- Up to 65 pages per minute printed, folded, sealed and ready to mail

## Benefits

- Reduce operating costs
- Eliminate the cost of the inventory of envelopes
- Streamline your entire mailing process
- Professional results without the high costs
- Secure document processing

# PSMailers IN-LINE 6400-6

## Prepare Mailings – Easily and Efficiently

Print, fold, and seal all in one step with the new **PSMailers IN-LINE 6400-6**. This streamlined system brings a superb cost-to-value ratio and delivers up to 65 mail-ready pieces per minute.



By pairing with HP technology, the **PSMailers IN-LINE 6400-6** also offers secure professional printing.

**Target Markets:** Education, Business, Government and Healthcare.

**Applications:** Checks, Tax Forms, Direct Deposit, Grade Reports, Transcripts, Utility Bills, Invoices, and much more.

## SPECIFICATIONS FOR THE IN-LINE 6400-6

<b>Duty Cycle</b>	Duty cycle of printer
<b>Warranty</b>	90 days
<b>Form Sizes</b>	8.5 x 11 or 8.5 x 14
<b>Types of Folds</b>	Z, EZ
<b>Physical Connection</b>	Aligns to the rear output tray of HP LaserJet 4014/4015/4515 series printers (4014/4015/4515TN require additional riser)
<b>Engaging the Device</b>	Manual, connection when docked
<b>Jam Recovery</b>	Rollers have a manual advance, access panels make media removal simple
<b>Jet Link</b>	Communications package stops printer if jam occurs
<b>Power Requirement</b>	100 to 127 Volt, 50/60Hz; 200 to 240 Volt, 50/60 Hz
<b>Dimensions</b>	W x D x H (output bin retracted): 15.5 x 19 x 15 inches; W x D x H (output bin extended): 15.5 x 21.75 x 16.5 inches
<b>Weight</b>	50 lbs. shipping weight
<b>Supported Printers</b>	HP LaserJet 4014, 4015, 4515 Series Printers; Also <b>6400:</b> 4000, 4050, 4100 <b>6400-1:</b> 4200, 4250, 4300, 4350 <b>6400-5:</b> M601, M602, M603 <b>6400-6:</b> M604, M605, M606